

ECOL MOTOR
MODEL D1S 250M1-2
TECHNICAL DATA SHEET

General Data	
Frame size	250
Housing material	Casting iron
Install model	According to the standard
Type of feet	Removable feet (Standard) Fixed feet (Optional)
Net weight	391 kg
Insulation class	F (Standard)
	H (Optional)
Protection degree	IP 55 (Standard)
	IP 56 (Optional)
Thermal protection	Without (Standard)
	Customizable (Optional)
Rotation direction	Clockwise (Standard)
	Counter clockwise (Optional)
Service duty	S1
Vibration level	A
Balance	Half-key balanced
Cable glands	2 - M50x 1.5
Cooling	IC 411
Painting color	RAL 7024 (Standard)
	Customizable (Optional)
Regulations	IEC / DIN / ISO / VDE / EN
Standard	IEC 60034

Environmental conditions	
Ambient temperature	From -20°C to +40°C
Maximum altitude	1000 m above sea level

Electrical Data		
Output	55	kW
Frequency	50	Hz
Voltage (±5%)	400	V Δ @ 50Hz
	690	V Y @ 50Hz
	480	V Δ @ 60Hz
	828	V Y @ 60Hz
Rotation speed	2930	RPM @ 50Hz
	3516	RPM @ 60Hz
Rated current	97.95	A (In) @ Δ 50Hz
	56.55	A (In) @ Y 50Hz
Starting current	7.5	xIn
Rated torque	179.27	Nm (Mn)
Starting torque	2	xMn
	2.3	xMn
Efficiency	IE1	
	92.1	@ 100% load
	92.5	@ 75% load
Power factor cosφ	90.7	@ 50% load
	0.88	@ 100% load

Mechanical Data		
Bearings brand	C&U	(Standard)
	Customizable	(Optional)
Bearings type	6314 C3	(DE)
	6314 C3	(NDE)
Lifetime of bearings	- hours	
Allowed radial load	4641 N	
Allowed axial load	45300 N	
Grease type	polyurea-based grease	
Lubrication interval of NDE bearing	4000 h	
Lubrication interval of DE bearing	4000 h	
Moment of inertia	0.389030	Kg*m ²
Noise level	93	dB(A)

