

**ECOL MOTOR**
**MODEL D1S 315L2-2**
**TECHNICAL DATA SHEET**

General Data	
Frame size	315
Housing material	Casting iron
Install model	According to the standard
Type of feet	Removable feet (Standard) Fixed feet (Optional)
Net weight	1070 kg
Insulation class	F (Standard)
	H (Optional)
Protection degree	IP 55 (Standard)
	IP 56 (Optional)
Thermal protection	Without (Standard)
	Customizable (Optional)
Service duty	S1
Vibration level	A
Balance	Half-key balanced
Cable glands	2 - M63x 1.5
Cooling	IC 411
Painting color	RAL 7024 (Standard)
	Customizable (Optional)
Regulations	IEC / DIN / ISO / VDE / EN
Standard	IEC 60034

Environmental conditions	
Ambient temperature	From -20°C to +40°C
Maximum altitude	1000 m above sea level

Electrical Data		
Output	200	kW
Frequency	50	Hz
Voltage ( $\pm 5\%$ )	400	V $\Delta$ @ 50Hz
	690	V Y @ 50Hz
	480	V $\Delta$ @ 60Hz
	828	V Y @ 60Hz
Rotation speed	2945	RPM @ 50Hz
	3534	RPM @ 60Hz
Rated current	345.06	A (In) @ $\Delta$ 50Hz
	199.21	A (In) @ Y 50Hz
Starting current	7.1	$\times$ In
Rated torque	648.56	Nm (Mn)
Starting torque	1.8	$\times$ Mn
Breakdown torque	2.2	$\times$ Mn
		IE1
Efficiency	94	@ 100% load
	94.3	@ 75% load
	93.1	@ 50% load
Power factor $\cos\phi$	0.89	@ 100% load

Mechanical Data		
Bearings brand	C&U	(Standard)
	Customizable	(Optional)
Bearings type	6317 C3	(DE)
	6317 C3	(NDE)
Lifetime of bearings		- hours
Allowed radial load		6800 N
Allowed axial load		64700 N
Grease type	polyurea-based grease	
Lubrication interval of NDE bearing		3200 h
Lubrication interval of DE bearing		3200 h
Moment of inertia	1.906230	Kg*m <sup>2</sup>
Noise level	99	dB(A)

